

MT Ferrule



This ferrule that connects multicore optical fiber in a batch with high accuracy and high density.

Multimode and single mode with various core number are lined up.

Characteristics

- Application for multi-core optical fiber.
- There are two ways to connect, using a mating pin and a clip, or using it in MPO/MTP.
- Available for multimode and single mode.

Specification

Product name	grade	Insertion loss	Applied Polishing
4MT-R	SM	0.7dB	Flat
8MT-R	SM	0.7dB	Flat
8MT-PA-S	SM	0.7dB	Angled PC
8MT-PA-SLS	SLS	0.35dB	Angled PC
12MT-PF-M	MM	0.5dB	Flat PC
12MT-PF-SLM	SLM	0.35dB	Flat PC
12MT-PA-S	SM	0.7dB	Angled PC
12MT-PA-SLS	SLS	0.35dB	Angled PC
16MT-PF-M	MM	0.5dB	Flat PC
16MT-PA-S	SM	0.7dB	Angled PC (Under development)
24MT-PF-M	MM	0.5dB	Flat PC
24MT-PF-SLM	SLM	0.35dB	Flat PC
24MT-PA-S	SM	0.7dB	Angled PC
32MT-PF-M	MM	0.5dB	Flat PC
2mini-MT-M	MM	0.5dB	Flat PC

※PC is Physical contact polishing.

- We provide MPO kit by Woojin and MTP kit by USconec. Your enquiry is expected.
- Providing available of MT ferrule that is flat polished type and also clip and mating pin.